

# Single-Layer Acoustic Curtains

Soundabsorbing Curtains providing  
certified flammability and absorption



Project: Gemeindesaal Katharina von Bora, Rüsselsheim


A pleasant room acoustics is a prerequisite for relaxed entertaining and efficient work. These high-quality acoustic curtains improve the speech intelligibility in meeting rooms and increase the ability to concentrate in working- and

class-rooms. All of our curtains are flame-retardant, washable and fulfil the Oeko-Tex Standard 100 and are therefore suitable for many applications in public areas. All curtains are tailor-made individually – for this reason custom

designs are not only possible without difficulty but a feature of our day-to-day working. Sewing is included in the price, our customers receive a ready-made curtain.

## Specifications Acoustic Curtains AV10, AV12, AV13 und AV15

<b>Application</b>	Control- and recording rooms, cinemas, call centers, offices and residence areas, seminar rooms and classrooms, daycare centers and schools, event and concert rooms, clinics and offices, restaurants
<b>Material</b>	100% polyester (Trevira CS), dyed environmentally-friendly, no release of toxic gases, tested for harmful substances according to Oeko-Tex Standard 100, very good UV stability
<b>Processing</b>	tailor-made to size, seams on the sides, a pocket for lead tape at the bottom, sewed heading tape at the top
<b>Cleaning</b>	washable at 60°C
<b>Flammability</b>	permanently flame retardant according to DIN 4102 B1



	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz
AV10	0,06	0,21	0,60	0,82	0,81	0,83
AV12	0,08	0,33	0,68	0,78	0,83	0,90
AV13	0,05	0,45	0,90	0,90	0,85	0,85
AV15	0,11	0,55	1,02	1,06	1,02	1,06

Sound Absorption  
AV10, AV12, and AV13: drapery 170%, distance to back wall 15 cm  
AV15: drapery 200 %, distance to back wall 10 cm



Certificates acc. to  
DIN EN ISO 354: 2003

### AV10 „Acoustic-Satin“

opaque satin

**Weight**  
200 g/m<sup>2</sup>

**Colour**  
Colour Card AV10  
containing 32 colours

**Sound Absorption**  
Certificates for 15, 30, 45  
and 60 cm distance to back  
wall, drapery 170 %  
up to class D (EN ISO 11654)  
 $w = 0,45$

### AV12 „Acoustic-Velvet“

heavy velvet, black-out

**Weight**  
370 g/m<sup>2</sup>

**Colour**  
Colour Card AV12  
containing 24 colours

**Sound Absorption**  
Certificates for 15, 30, 45  
and 60 cm distance to back  
wall, drapery 170 %  
up to class C (EN ISO 11654)  
 $w = 0,65$

### AV13 „Acoustic-Dimout“

dobby, black-out

**Weight**  
330 g/m<sup>2</sup>

**Colour**  
Colour Card AV12  
containing 19 colours

**Sound Absorption**  
Certificate for 15 cm distance  
to back wall, drapery 170 %  
up to class C (EN ISO 11654)  
 $w = 0,75$

### AV15 „Theatre-Velvet“

extra-heavy velvet, black-out

**Weight**  
520 g/m<sup>2</sup>

**Colour**  
Colour Card AV12  
containing 28 colours

**Sound Absorption**  
Certificate for 10 cm distance  
to back wall, drapery 200 %  
up to class A (EN ISO 11654)  
 $w = 0,95$